



## megaTower Plus 6M4T

Model	FWMT-0885-HVPA-07670648
Total Energy Capacity [kWh]	885
Usable Energy, 90% DoD [kWh]	796
Recommended Energy per Cycle, 80% DoD [kWh]	708
Battery Current Capacity [Ah]	320x4
Nominal Voltage [V] <sup>1</sup>	691
Max/Min. Operating Voltage [V]	767/648
Max/Cont. Discharge Current [A] <sup>2</sup>	880/800
Max/Cont. Discharge Power [kW]	605/553
Max/Cont. Charge Current [A] <sup>2</sup>	640/384
Max/Cont. Charge Power [kW]	442/265
Crated Weight [kg]	Frame: 530   Isolation Panel: 98   Busbars: 58   Modules: 284
Total Weight - Including Rack [kg]	5984
Overall Dimensions - H x W x D [mm] <sup>3</sup>	1559x5071x714
Crated Dimensions - H x W x D [mm]	Frame: 780x1700x1740   Isolation Panel: 1046x596x486   Busbars: 120x140x4060   Modules: 422x1320x772
Module and Cell Configuration	36 Cells per module in series, 6 modules in series per tower. 4 parallel towers per battery
Module Weight [kg]	234
DC Connection	Busbar in isolator cabinet - installer to connect appropriate cables
DC Connection - Fly Leads (no. per electrode) [mm <sup>2</sup> ]	2 x 95mm <sup>2</sup> Polybraid Cable
Module Enclosure	Mild Steel – powder coated white, IP54 enclosure rating, rack mounted to suit racks on both walls inside 12m long High Cube shipping containers with centre aisle. Note: Container floor might require reinforcement, container weight limitations apply for transport
Protection	Main bank fuses (1000A), fuses in each module (400A), contactors in each master module. Protection against short circuits, overcurrent, cell under and over voltage and temperature, weak cell detection
Control Interface	CAN Bus, Ethernet/Gateway
Human Interface	RJ45 plug for programming or PC access, On/Off button with indicator light
Remote Monitoring	Real time data logging and remote monitoring over Ethernet. Internet connection required
Service Life <sup>4</sup>	Standard Warranty: 10 year (or 8000 cycles) 80% DoD, 0.5C Max Discharge, 0.3C Continuous Discharge, 0.3C Max Charge, Max 25deg. Expected life: >15 yrs (>8000 cycles) at 80% DoD
Battery Standards	Designed and built according to IEC62619, IEC62040, IEC61000, UN38.3

### Notes to Specification Sheet

1. Voltage suitable for various high DC voltage inverters. Please enquire with Freedom Won for pairing support.
2. Max current duration 2 min every 10min. 1.5 x Max overload can be handled for 5 seconds. Current limits rated for 10°C to 25°C battery temperature. Derating will apply outside this temperature range.
3. These dimensions do not include the isolation panel on the side. Power supply and isolation panel dimensions H x W x D [mm] 930x440x370mm. Isolation panel door opens towards the front face of the megaTower. Isolation panel can be mounted either side of the megaTower.
4. Refer to warranty document for further details.
5. Isolation panel requires 220VAC to ensure the backup batteries are charged and balanced.

#### DISTRIBUTORS AND RESELLERS

Contact your nearest Accredited Freedom Won Distributor or Accredited EPCs for further sales and technical support.

Plug into The Current Future

[www.freedomwon.co.za](http://www.freedomwon.co.za)